

## **Bubbles in Sediments**

**Steven G. Kargl**

Applied Physics Laboratory

University of Washington

1013 NE 40th St.

Seattle, WA 98105

Phone: (206) 685-4677 FAX: (206) 543-6785

Email: kargl@apl.washington.edu

Award #: N00014-96-1-0159

### **SHALLOW-WATER ACOUSTICS**

#### **LONG-TERM GOAL**

This research investigated the scattering of an acoustic field from a bubble embedded in a saturated sediment. The primary objective was to establish the underlying physical mechanisms of resonance scattering near the breathing mode (or monopole) resonance.

#### **SCIENTIFIC OBJECTIVES**

Bubbles are known to be present in naturally occurring sediments particularly in littoral regions, and it has been proposed that these bubbles are primary contributors to volume scattering of sediment penetrating sonars.

#### **APPROACH**

The scattering from an isolated bubble in an infinite, isotropic, homogeneous sediment was analyzed where the sediment was modeled as either an effective fluid, effective viscoelastic solid, or a saturated poroelastic medium. The analysis included only the breathing mode resonance because this resonance dominates the dynamics of the bubble. The complexity of wave propagation in the choice of model for the sediments increases in the order given.

Based on the results of the theoretical treatment, a laboratory experiment has been designed to test which model provides a suitable characterization of the underlying wave propagation and scattering phenomenon. The experiment embeds a bubble in a synthetic, transparent sediment. This sediment is prepared by matching the optical indices of refraction of soda-lime glass beads, which represent grains of sand, and a saturating fluid. The forward extinction of a HeNe laser by an acoustically driven bubble is characterized by a modulations in the optical intensity. The frequency of modulation is directly related to the dynamics of the bubble.

#### **WORK COMPLETED**

To date, the theoretical treatment has been completed and documented[1]. A brief description of the main results are discussed below.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>30 SEP 1997</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-1997 to 00-00-1997</b>	
4. TITLE AND SUBTITLE <b>Bubbles in Sediments</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>University of Washington, Applied Physics Laboratory, 1013 N.E. 40th Street, Seattle, WA, 98105</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>3</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

Experimental verification of theoretical predictions has progressed to the measurement of the optical extinction. A synthetic transparent sediment has been constructed from nominally 300 micron glass beads obtained from Cataphote Inc. The beads are saturated with immersion liquid code 1160 from Cargille Laboratories Inc. Although the saturated beads are not perfectly clear to white light, an embedded bubble is visible and the principal laser line from a HeNe laser (632.8 nm) passes through a small volume without much loss. The experiment is scheduled to be completed in early FY98.

## **RESULTS**

If a sediment can be characterized by an effective fluid model, then theory predicts a bubble will support a breathing mode resonance on the order of a few kHz in agreement with the well-known Minnaert resonance frequency. The viscoelastic solid model for a sediment predicts a much higher resonance frequency due primarily to the inclusion of shear rigidity in the model. It is noted that both an effective fluid model and an effective viscoelastic solid model predict a single breathing mode resonance, and the frequency of this resonance are widely separated for each model. Finally, if a sediment is modeled by Biot theory, which describes wave propagation in a saturated poroelastic medium, then two monopole resonances are predicted. These resonances appear to be an intrinsic property of Biot theory, and hence, can validate the application of Biot theory to sediment acoustics. The predicted resonance behavior under each model is distinct, so an optical extinction measurement may provide an unambiguous measure of which model(s) applies.

## **IMPACT/APPLICATION**

Bubbles are known to occur in natural sediments. It is expected that the knowledge gained in this research will impact sediment penetrating sonar systems and the interpretation of images produced by these sonars.

## **TRANSITIONS**

The present research will be extended from single isolated bubbles to multiple bubbles where multiple scattering becomes important. Additionally, the infinite medium assumption imposed to isolate the resonance behavior will be removed such that the bubble will be embedded in a plane stratified medium of arbitrary composition. These extensions are expected to transition into enhancement to sonar prediction tools such as the Shallow Water Acoustic Toolset (SWAT) available from the Coastal Systems Station, Dahlgren Division, Naval Surface Warfare Center.

## **RELATED PROJECTS**

The current research has a potential impact on the Departmental Research Initiative (DRI) entitled High-Frequency Sound Interaction in Ocean Sediments under the sponsorship of ONR Code 321 Ocean Acoustics. The DRI is addressing the sub-critical penetration of

sonars into sand sediments. One hypothesis for this penetration is the interaction of volume inhomogeneities with the evanescent field near the sediment-water interface.

## REFERENCES

- [1] S.G. Kargl, K.L. Williams, and R. Lim, Double monopole resonance of a gas-filled, spherical cavity in a sediment,"*J. Acoust. Soc. Am.*, in press.